



Hiview-PC3W

3MP Outdoor Full-color Active Deterrence
Fixed-focal Wi-Fi Pan & Tilt Network Camera

Series Overview

The PC3W series of small PT cameras raises the bar on performance. After detecting an intrusion, it triggers sound and light alarms, and then instantly relays vital information on the intrusion to the mobile client, keeping you informed no matter where you are. It supports two-way talk, allowing you to communicate with people in front of the camera in real time. It also can record full-color videos and information of key events using Smart Dual Illuminators, effectively reducing light pollution.



3MP

Clear images with sharp details



Smart Dual Light

Captures color details for post-event review



One Camera for 360° View

360° monitoring without blind spots



Sound and Light Alarm

Provides instant alarms to deter intruders



AI Human Detection

Focuses on what matters and reduces false alarms



AI Vehicle Detection

Focuses on what matters and reduces false alarms



Preset Patrol

Guards the places that matter to you regularly



Auto Tracking

Automatic tracking of targets



Abnormal Sound Alarm

Detects abnormal sounds and sends alarms in time



IP65 Protection

Withstands harsh environments



Wi-Fi 6

Seamless integration of speed and anti-interference



Bluetooth Pairing

Fast pairing with Bluetooth



H.265

Advanced H.265 compression technology



SD Card

Low-cost storage

Specifications

Camera

Image Sensor	1/2.7" CMOS
Max. Resolution	2304 (H) x 1296 (V)
Electronic Shutter Speed	Auto/Manual 1/3 s–1/100,000 s
Illumination Distance	Up to 30 m (98.43 ft) (IR); Up to 30 m (98.43 ft) (Warm Light)
Illuminator On/Off Control	Auto
Illuminator Number	2 (IR LED); 2 (Warm light)
Angle Adjustment	Pan: 0°–355°; Tilt: 0°–65°

Lens

Max. Aperture	F1.6
Field of View	H: 87°; V: 44°; D: 105°

Intelligence

Vehicle Detection	Yes
Human Detection	Yes

Video

Video Compression	H.265
Video Frame Rate	Main stream: 2304 x 1296@(1-25/30 fps) sub stream: 640 x 360@(1-25/30 fps) *The values above are the max. frame rates of each stream; for multiple streams, the values will be subjected to the total encoding capacity.
Resolution	3M (2304 x 1296); nHD (640 x 360)
Video Bit Rate	H.265: 80 kbps–4096 kbps
Day/Night	Auto(ICR)/Color/B/W
WDR	DWDR
Motion Detection	Yes
Smart Illumination	Yes

Image Rotation

0°/180°

Audio

Built-in MIC	Yes, built-in Mic
Built-in Speaker	Yes, built-in speaker

Audio Compression

G.711a

Network

Network Port	RJ-45 (10/100 Base-T)
Wi-Fi	IEEE 802.11b/g/n 2.4–2.4835 GHz, 2.4 G
Storage	Micro SD card (up to 256 GB)
Management Software	Hiview Connect
Mobile Client	iOS;Android

Power

Power Supply

12 VDC

Power Consumption

Basic: 1.56 W;
Max.: 4.56 W (H.265+warm light on)

Environment

Operating Temperature

–20 °C to +50 °C (–4 °F to +122 °F)

Operating Humidity

≤95%

Structure

Casing Material

Plastic

Product Dimensions

116 mm x 138 mm x 139 mm (4.57" x 5.43" x 5.47")
(L x W x H)

Net Weight

425 g (0.94 lb)

What's in the box

