

POE SWITCH

HiView 16 PORT AI POE SWITCH

HIK 6016



- 16 RJ45 ports with 10/100Mbps PoE function (ports 1 to 16)
- 2 RJ45 ports with 10/100/1000Mbps non PoE functionality (ports 17 to 18)
- 1 Gigabit SFP fiber optic port (multiplexing)
- Stable and highly reliable operation of equipment
- Air cooling and heat dissipation, intelligent speed regulation, low noise and energy-saving

Overview

The product has 16 100M PoE ports, 2 gigabit RJ45 ports and 1 gigabit SFP Combo port

Switch backplane bandwidth 7.2Gbps	Packet forwarding 5.4Mpps	switch port 16 RJ45 ports with 10/100Mbps
Working Humidity 10% ~ 90% RH non-condensing	Dimensions (W × D × H) 285mm*180mm*44mm	2 RJ45 ports with 10/100/1000Mbps 1 Gigabit SFP fiber optic port (multiplexing)

Specifications

Network Interface	• 16 * 10/100Mbps RJ45 PoE Ports (Port 1~Port 16) • 2 * 10/100/1000Mbps RJ45 Ports (Port 17~Port 18) • 1 * SFP Combo Port
Network protocol	• IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at
Performance Specifications	• Backplane Bandwidth: 7.2Gbps (non-blocking) • Packet forwarding rate: 5.4Mpps • MAC address table: 8K • Forwarding mode: store and forward
LED Indicator	• Power indicator: 1 • LINK/ACT indicator: 18 • PoE indicator: 16
PoE foot position	• 1/2(+) , 3/6(-)
Power support	• Single port maximum output power: 30W • The maximum power of the whole machine: 150W
Physical Specifications	• Dimensions (LxWxH): 285mm*180mm*44mm
Environmental Specifications	• Operating temperature: 0°C~40°C • Storage temperature: -40°C ~ 70°C • Working humidity: 10%~ 90% RH without condensation • Storage humidity: 5%~90% RH without condensation
Safety regulations	• CE/ROHS/FCC/CCC

Networking Application:

